


Spartec Conveyors

17181 LANDWER CT, SPRING LAKE, MI 49456
616-846-4300 • www.q-1enterprises.com

CONVEYORS ••• PARTS • SCRAP • PACKAGE • BULK HANDLING

HINGED STEEL BELT CONVEYORS

4" Pitch



SECTION VIEW

SPECIFICATIONS

WIDTHS: 6" Thru 36" Belt

FRAME: 15" x 10 Ga Formed Steel Channel

HEAD SPROCKETS: 6 Tooth x 5" Pitch Dia Cast Iron

TAIL SPROCKETS: 6 Tooth x 5" Pitch Dia Cast Iron

BEARINGS: Anti-Friction Ball Bearing

DRIVE: Top Mount, Roller Chain From Reducer to Headshaft

MOTOR: 1725 RPM, 56 C-Face, TEFC

REDUCER: Right Angle 56 C-Face

BELT: 2 1/2" Pitch x 12 Ga Hinged Steel Apron, Plain / Pimpled or Perforated, 7/16" Dia
1045 CRS Shafts, 10 Ga Interlocking Side Wings, 1 1/2" Dia x 3/4" Hardened Steel
Rollers. Optional 3/16" x 1" Side Bars, 1/4" x 1 1/2" Cleats

CONTROLS: As Required